

British Standard Pipe Parallel – Port Connection


British Standard Pipe Parallel (**BSPPOR**) Connection Types / Identification

This series (G) contains BSPP Parallel Port Connectors with a washer / o-ring seal included. For a more complete series of BSPP adapters, most all males in series (B) can be used as a Port Connection with the addition of a bonded seal.


Measurement Procedure

1. With calipers, measure the O.D. (outside diameter) of the Male threads or the I.D. (inside diameter) of the Female Threads.
2. Check the thread pitch with the thread pitch gauge.
3. Compare measurements against chart.


Dash Size	Nominal Size	Thread Pitch	Male Thread O.D. (inches)		Female Thread I.D. (inches)	
2	1/8	28	.375	3/8	.344	11/32
4	1/4	19	.531	17/32	.469	7/16
6	3/8	19	.656	21/32	.594	19/32
8	1/2	14	.813	13/16	.750	3/4
12	3/4	14	1.031	1-1/32	.969	15/16
16	1	11	1.938	1-15/16	1.219	1-13/16
20	1-1/4	11	1.656	1-21/32	1.531	1-17/32
24	1-1/2	11	1.875	1-7/8	1.781	1-25/32




**Male BSPP
Port Connection
(Washer / O-Ring)**



**Male BSPP
Port Connection
(Bonded Seal)**



**Male BSPP
Port Connection
(Captive Seal)**



**Female BSPP
Parallel Port**