



Malone Specialty Inc.
 8900 East Ave., Mentor, Ohio 44060
 Phone: 800-874-3077 ~ Fax:800-874-3066
sales@malonespecialtyinc.com

NSSC Sockets

Hose Bore / Dash Size	R1AT/1SN Crimp OD		R2AT/2SN Crimp OD		R16/2SC Crimp OD	
	mm	inch	mm	inch	mm	inch
3/16" (-3)	15.8mm	0.622"	16.4mm	.646"	N/A	N/A
1/4" (-4)	17.3mm	0.681"	18.4mm	.724"	17.7mm	.698"
5/16" (-5)	18.4mm	.724"	19.3mm	.76"	19mm	.748"
3/8" (-6)	19.4mm	.764"	20.6mm	.811"	19.7mm	.776"
1/2" (-8)	22.2mm	.874"	23.4mm	.921"	22.4mm	.882"
5/8" (-10)	26.3mm	1.035"	27.2mm	1.071"	26.5mm	1.043"
3/4" (-12)	29.8mm	1.173"	31.2mm	1.228"	30.2mm	1.189"
1" (-16)	37.7mm	1.484"	39mm	1.535"	38.7mm	1.524"
1 1/4" (-20)	47.1mm	1.854"	49.6mm	1.953"	N/A	N/A
1 1/2" (-24)	54.4mm	2.142"	56.3mm	2.217"	N/A	N/A
2" (-32)	67.3mm	2.65"	69.3mm	2.728"	N/A	N/A

Notes

Crimp the entire length of the socket

Tolerance = 0/-.2mm